



# RAIN-MATE

## All Weather General Purpose Sealant

### Description

*A water repellent, general purpose sealant, based on SBR rubber. It has excellent adhesion to all surfaces, even when damp.*

### Uses

Bond It **RAIN-MATE** is a permanently flexible, water repellent and UV resistant, paintable sealant that will not crack or slump.

It suitable for use on brick, concrete, stone, all metals, painted or bare wood, glass, vinyl and most plastics. It is also compatible with bitumen and asphalt for roof repairs in damp conditions.

It is ideal for sealing doors, windows, roofs, cladding and vehicle bodies.

### Application

Primers are not usually required.

Rust, etc, should be removed to give as sound a surface as possible. For application in damp conditions remove any standing water and residual dirt and dry the surface as well as possible with cloths or paper towels before applying sealant. Apply the sealant in a normal fashion ensuring there is sufficient sealant present to accommodate any future joint movement (25% of sealant width). Allow 24 hours before painting.

All **RAIN-MATE** colours will adhere to bitumen and asphalt but we only recommend black for this purpose as unsightly discolouration can occur with white and clear.

### Cleaning

Clean tools immediately using Bond It uPVC Solvent Cleaner.

### Limitations

Not for use on expanded polystyrene, polycarbonate, plastic roof lights or other solvent sensitive surfaces. Do not apply at over 60°C or on surfaces which exceed 80°C in use.

### Container Size

EU3 plastic cartridge.

### Colours

**RAIN-MATE** comes in 3 colours: black, clear, and white.

### Shelf Life

Minimum 12 months in unopened cartridge.

### Storage Conditions

Store in cool, dry conditions.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

*Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.*

## Specification Summary

Flammability	Flammable
Skinning Time	15 minutes
Full Cure	24 hours before painting, full cure dependent on depth
Joint Movement	Plus or minus 25%
Specific Gravity	0.95
Flash Point	Approx 25°C
Viscosity	Approx. 800 poise @ 25°C
Evaporation Rate	<25
Solvent Content	23%

### Container Sizes:

<b>Code:</b>	BDAWSCL	BDAWSWH	BDAWSBL
<b>Colour:</b>	Clear	White	Black
<b>Size:</b>	EU3	EU3	EU3
<b>Barcode:</b>	5060021360502	5060021367891	5060021362612

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number: 6152  
ISO 9001  
ISO 14001



**BOND IT**  
Units G16, 17 & 18 River Bank Way, Lowfields Business Park,  
Elland, West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 18/6/18  
Supersedes V1 1/5/17