



Never compromise on quality!



GLUE MONSTER SUPERGLUE

Description

An all purpose, premium grade cyanoacrylate adhesive, that provides a high strength, rapid bond to almost any surface or materials.

Uses

BOND IT **SUPERGLUE** will bond metals, wood, ceramics, plastic, porcelain, leather, cardboard, and much more.

Preparation

Surfaces to be bonded should be clean, dry and free from dust and grease.

Application

Items being bonded must be a perfect fit. Apply the adhesive sparingly to one surface only (do not over apply). Assemble the items immediately and press firmly for 30 seconds. After use, clean the nozzle of the tube with a dry cloth or paper roll and firmly screw the cap back onto the tube.

Note: Take care when aligning the treated objects as once the surfaces have been brought together an instant bond will be formed.

Limitations

Do not use on surfaces that bleed oils or plasticisers. Not suitable for permanent bonding of glass. Olefinic or fluoro polymers may require specialised bonding techniques.

Storage Conditions

Store in cool, dry conditions at a temperature of between 0°C and +20°C. Storage outside these parameters will dramatically reduce the shelf life.

Shelf Life

Minimum shelf life 12 months.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local

regulations.

Cleaning

Uncured material can be removed using acetone or nail varnish remover (protect any surrounding surfaces from potential spillages).

Health & Safety

**Contains: ethyl-2-cyanoacrylate.
Danger Cyanoacrylate Adhesive.
Bonds skin and eyes in seconds.**

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Specification Summary

Chemical Composition	Ethyl Cyanoacrylate
Flash Point	>85°C
Flammability	Capable of combustion
Boiling Point	>150°C
Solubility in Water	Polymerises
Grab	Very high initial grab
Appearance	Colourless liquid of medium viscosity
Viscosity	1400-1700 MPa.s
Specific Gravity	1.06g/cm ³
<u>CURED ADHESIVE</u>	
Gap Filling	Up to 0.25mm
Peel strength canvas-canvas, 48hr	>30 N/cm ²
Shear strength wood-wood	>2 MPa
Service Temperature Range	-60 to +60°C

Container Sizes:

Code:	BDCSGC
Size:	3g x 12
Colour:	Clear
Barcode:	5060021366399

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V1 04/02/19
Supersedes:

