

**CTA FLEXIBLE
NOW AVAILABLE IN GREY**



PART OF THE PROFESSIONAL TILING RANGE

A grey, cement based, flexible ceramic floor and wall tile adhesive with built in admix. Conforms to EN 12004 Type C2 T E S2. Suitable for large format and porcelain tiles.

A standard setting cement based tile adhesive that offers high grab, non-slip and flexibility. Suitable for use in areas subject to limited movement and vibration and with all types of ceramic floor and wall tiles, mosaics, porcelain, natural stone, marble and travertine tiles onto substrates including; underfloor heating, tile on tile and properly prepared sheeted timber. It is water resistant making it suitable for use in bathrooms, saunas and swimming pools.

Benefits:

- **Excellent bond strength and high grab.**
- **Water resistant.**
- **Flexible / non-slip.**
- **Suitable for ceramic, porcelain, vitrified and natural stone tiles.**
- **For internal and external use.**
- **For floor and wall tiles.**
- **CE Approved.**

Specification Summary

Bed Thickness	3 to 6mm
Pot Life	4 to 5 hours
Grout After	12 hours
Light Traffic	12 hours
Full Traffic	24 hours
Coverage	Approx 6 - 7m ² @ 3mm bed thickness
Conforms to	EN 12004 Type C2 T E S2



Code	Colour	Box	Size	Barcode
BDCTAF20GR	Grey	1	20Kg	5056437401489

