



Never compromise on quality!



SBR ADMIXTURE

Mortar/rendering Admixture and Bonding Agent

Description

A premium grade SBR designed to give concrete floors and cement renders abrasion, chemical and water resistance. Bond It SBR also shows improved performance as a key coat adhesive compared to non SBR bonding agents.

Uses

For improving a mortar's, render's or floor screed's abrasion and chemical resistance. Providing protection during continued or intermittent water contact suitable for both external or internal use application. Key coat applications to substrates with a low porosity. For repair patching of concrete and cement screeds, to improve adhesion and flexibility of screeds.

Application

All surfaces should be free from laitance, oil, grease and standing water. Unsound surfaces should be scabbled down to a solid base material.

Key Coat: Mix 1 part Bond It SBR to 2 parts cement by volume and adjust to brushable consistency with water. Mix only enough to use within the hour. Brush thoroughly into a clean dust free substrate, whilst still wet overcoat with the floor or render mix.

Damp-proofing: Mix the same formulation as in the key coat and apply the first coat with vigorous brush strokes. Allow to touch dry then apply a second coat at 90° to the first and allow 48 hours to dry. Apply the third coat at 90° to the second coat and while still wet apply the render.

Renderings/Mortars: Prepare the substrate with the key coat first for best results. Mix sand/cement mortar/render and add 5-7.5 litres Bond It SBR per 25Kgs cement, reducing the amount of gauging water accordingly. Apply at least 6mm thick. Two coats are recommended.

Granolithic Floorings: Prepare the substance with the key coat first for best results. Mix cement: sand: 3mm granite flooring chips 1: 1½: 1½ Use 5L Bond It SBR to each 25Kg of cement, for floors up to 25mm thick. For floors greater than 25mm use 2.5 litres Bond It SBR and add water accordingly to produce a semi-dry mix.

Patching Concrete: Use the key coat and use a 3:1 render mix feathering lightly.

Limitations

Protect from freezing. Do not use with cements other

than OPC without first contacting the cement supplier. Do not use chloride based frost proofers with Bond It SBR. Do not over mix mortar/render.

Storage Conditions

Store in cool, dry conditions. Protect from frost, high temperature and sunlight.

Shelf Life

Up to 24 months when stored according to manufacturers instructions.

Coverage

Flooring: 5 litres SBR for every 25Kgs cement.
Mortar/Rendering: 5-7.5 litres SBR for every 25Kgs cement.

Key Coat: 5 litres SBR per 30m² depending on porosity.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Avoid eye contact. In the event of contact irrigate eyes immediately with plenty of cold, clean water for 15 minutes and seek medical attention.
- ◆ Avoid prolonged contact with skin. Wear wellington boots, protective clothing and gloves.
- ◆ Do not ingest. In the event of ingestion, do not induce vomiting, drink plenty of water and seek medical attention.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs discontinue use.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Appearance	Milky White Liquid capable of florescence
Flammability	Non Flammable
pH	approximately 10.5
Solubility in water	Soluble
Boiling Point	100°C (water)

Container Sizes

Code:	BDH039	BDH040	BDH041	BDH042
Size:	2.5L	5L	25L	200L
Barcode:	5060021371454	5060021361196	5060021361202	5060021364234

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V3 04/1/16
Supersedes V2 11/8/15

