



Never compromise on quality!



FLASH-MATE

Low Modulus Lead Sealant

Description

A high performance neutral cure silicone sealant specifically designed for use with roofing products both modern and traditional, internally and externally.

Bond It **FLASH-MATE** is a low modulus neutral cure fast-skinning, roof sealant. It is designed to stop weather ingress, tile lift and noise. Complies fully with the requirements of **EN15651-1,2 F EXT-INT, G.**

Uses

Bond It **FLASH-MATE** is used to seal or bond dissimilar materials to prevent weather ingress. **FLASH-MATE** can be used to bond glass and glazing plastics as well as small sections of roofing materials under repair. Ideally suited for sealing rooflights, conservatories, soffits, glass houses, industrial roofing systems, lead flashing and to prevent tile lifting and wind noise.

FLASH-MATE is compatible with lead, galvanised steel and all metals. **FLASH-MATE** has excellent UV, heat and ozone resistance and sets to tough resilient rubber.

It is ideal for use on:

- ◆ glass
- ◆ slate
- ◆ all metals including lead and galvanised steel
- ◆ concrete and brick
- ◆ GRP
- ◆ sealed timber
- ◆ plastics (including polycarbonate)
- ◆ acrylics
- ◆ PVCu
- ◆ all painted surfaces

Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion. Priming may be necessary on porous surfaces.

Application

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed. Best tooling is achieved if a minute or two is allowed after application before smoothing. Polyethylene foam backing rod pushed into construction joints before sealing gives a technically superior joint and

minimises sealant consumption. For bonding press the two surfaces together before skinning commences. On very hot roofs skinning time will be much shorter.

Once the silicone has been applied and tooled rain will not have any adverse effects on the sealant.

Limitations

Porous surfaces should be primed first. Do not use on surfaces where water can penetrate through porous materials to the bond interface without first carrying out remedial work. Not suitable for use on natural stone.

Container Size

EU3 plastic cartridge.

Colours

FLASH-MATE comes in grey only.

Shelf Life

Use within 12 months from date of manufacture. Store in unopened cartridges.

Storage Conditions

Store in cool, dry conditions between 5°C and 25°C.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Specification Summary

Flammability	Non-flammable
Solubility in Water	Insoluble
Tooling Time	5-10 minutes
Skimming Time	15-25 minutes
Rate Of Cure	1-2mm per day
Joint Movement Capability	25% by ISO methods
Application Temperature	+5°C to +30°C
Service Temperature	-50°C to +120°C continuous exposure, higher temperatures can be withstood for limited periods

Container Sizes:

Colour:	Grey
Code:	BDLEAD
Size:	EU3
Barcode:	5060021363466



BOND IT	
G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9DN	
14	
EN15651-1,2: 2012 F EXT - INT, G	
Facade sealant for interior and exterior use	
Reaction to fire	E
Release of chemicals	None
Resistance to flow	≤ 3mm
Loss of volume	≤45%
Tensile properties after water immersion	≥25%
Durability	Pass

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park, Elland,
West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V6 20/5/20
Supersedes V5 21/6/18