



Never compromise on quality!



# ONE HIT WONDER LIGHTWEIGHT FILLER Gap-filling Compound



## Description

*A specially formulated compound consisting of millions of tiny glass bubbles that will fill most holes and gaps in a single application. Gives a super smooth, brilliant white finish that does not require sanding.*

## Uses

Bond It **ONE HIT WONDER** is suitable for use internally and externally, on uneven surfaces for delicate repair work and in areas which are difficult or awkward to fill e.g. ceilings. Effective for filling large holes in a single application as it is non-slumping and shrink resistant, which reduces the need to build up of layers of fillers.

This ready to use paste is suitable for use on:

- ◆ plaster
- ◆ concrete
- ◆ brick
- ◆ wood
- ◆ stone

## Preparation

Surfaces are clean, dry and free from any other contaminants that may hinder adhesion. To prevent rusting, any nail and screw heads must be covered with an oil-based primer prior to application.

## Application

Mix Bond It **ONE HIT WONDER** to a smooth paste. If it is too dry add a small amount of water and re-stir.

- ◆ Apply directly into the hole/gap, ensuring it is completely filled. Smooth the surface with a wetted pallet knife.
- ◆ Remove any excess material and allow to dry for at least 15 minutes (dependant on ambient temperature and gap size and depth.)
- ◆ Once dry, the filler can be sanded to give a smooth and even surface, if required.
- ◆ Where deep gaps have been filled the surface will dry in 15 minutes, however, care must be taken not to disturb the unset filler below the surface if over painting, etc.
- ◆ For outdoor applications, the gaps should be sealed with an oil-based paint. (When using oil based paints leave filler to dry for 12 hours).

- ◆ After use replace the plastic film and ensure lid is securely fixed in place. Wash any tools in warm soapy water.

## Limitations

Do not use in temperatures below 5°C or externally when rain is imminent. This product is not suitable for use in areas subject to continuous water immersion.

## Storage Conditions

Store in a cool, dry conditions and protect from frost.

## Shelf Life

Minimum 12 months.

## Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

## Safe Handling Precautions

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

*Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.*

## Specification Summary

Flammability	Non flammable
Chemical Composition	Acrylic based filler
Appearance	White paste
Solubility in Water	Soluble
pH	7-8
Boiling Point	100°C

### Container Sizes:

<b>Code:</b>	BDLWF4	BDLWF1	BDLWF05
<b>Size:</b>	4L	1L	500ml
<b>Barcode:</b>	5060021364791	5060021364807	5060021364814

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number: 6152  
ISO 9001  
ISO 14001



**BOND IT**  
Unit G16 River Bank Way, Lowfields Business Park, Elland,  
West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V5 11/02/16  
Supersedes V4 16/7/14

