



Never compromise on quality!



BUILD-MATE BUILDING MASTIC

Gunnable Pointing Mastic



MATE SEALANT & ADHESIVE RANGE

Description:

An oil based, gunnable pointing and sealing mastic for general exterior building use.

Benefits:

- ◆ *Sag resistant.*
- ◆ *Low toxicity.*
- ◆ *Self repairing skin.*
- ◆ *Does not harden under skin.*
- ◆ *Over paintable (*check compatibility with paint in a small area before full scale application).*
- ◆ *Adheres to most common building materials.*

Uses

Offers superior adhesion to all building surfaces and can be overpainted when fully cures with most conventional oil based paints. Weatherproof in most applications.

Bond It **BUILDING MASTIC** can be used to seal and bed window and door frames manufactured from metal or wood. It can also be used for the maintenance of low rise building joints, seals and flashing and for pointing around precast building materials.

Preparation

All surfaces must be clean, dry, sound and free from dust, oil, loose particles or any other contaminants that may hinder adhesion. Polythene tape or foam backing should be used in movement joints.

Application

Apply using a standard sealant gun. Cut tip from cartridge, be careful not to damage the screw thread. Cut the nozzle at an angle of 45° to an opening slightly larger than the gap to be sealed, and fix to cartridge. Force the mastic into the full depth of the joint, ensuring good contact with both sides.

The material may be tooled to a smooth finish using a wetted spatula, spoon or SEALANT APPLICATOR TOOL.



Tools can be cleaned using Bond It WHITE SPIRIT.

Limitations

Do not use on bitumen or asphalt or where joint movement exceeds 5% of mastic area.

Container Size

EU3 plastic cartridge.

Colours

BUILDING MASTIC is available in 3 colours - brown, stone and white.

Shelf Life

Minimum 2 years from date of manufacture when stored in unopened tubes.

Storage Conditions

Store in cool, dry conditions at a temperature between 5-30°C. Protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Flammability	Flammable
Sag	None
Joint Movement Accommodation	+/- 5% from mean position
Movement Joint Design	Min depth 12mm (1/2") Maximum width 25mm (1")
Filling	Min depth 4mm Min width 10mm

Product Details:

Colour:	White	Brown	Stone
Code:	BDOBWH	BDOBRR	BDOBST
Size:	EU3	EU3	EU3
Barcode:	5060021361592	5060021361578	5060021361585



Part of the Bond It Silicone & Sealants Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001
ISO 14001; ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 20/05/20
 Supersedes: V3 05/10/18