



Never compromise on quality!



PLASTERERS PREGRIT

Internal Plaster Bonding Agent



BUILDERS COMPLETE RANGE

Description:

A one part, ready-to-use internal plaster bonding agent with added aggregate to provide a key prior to plastering on smooth surfaces.

Benefits:

- ◆ *Bonding agent for smooth surfaces.*
- ◆ *Contains sand/aggregate to provide plaster key.*
- ◆ *Ready to use, one coat application.*
- ◆ *Perfect for use on smooth substrates.*
- ◆ *Pigmented yellow to identify treated areas.*
- ◆ *Phthalate free formulation.*

Uses

PLASTERERS PREGRIT should be used as a primer/ bonding aid prior to plastering on surfaces such as concrete, plaster and difficult, low or non-porous substrates. For internal use only, this product is not suitable for external applications.

Application

Thoroughly stir before use. Ensure all surfaces are clean, dry and free from any contaminants that may hinder adhesion, including any loose or flaking material. Ensure the background is sound and will support the weight of the plaster. Do not dilute. Simply apply one coat using a brush or roller and leave to dry for a minimum of 24 hours before plastering.

Note: cold or humid conditions will increase drying times. Do not use in temperatures below 5°C.

Limitations

- Do not use on areas subject to continual damp.
- Do not dilute.
- Do not exceed a maximum thickness of 25mm for complete render system.
- Remove any contamination of product to surrounding surfaces before drying.

Coverage

Depending upon surface porosity approx. 4-5m² / litre.

Container Size

10L and 5L plastic tubs.

Colour

Pale yellow.

Shelf Life

24 months from date of manufacture when stored in sealed tubs.

Storage Conditions

Store in cool, dry conditions in the original sealed container away from direct sunlight. Store between 5°C and 30°C.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations. Any spillages should be mopped up immediately with an inert absorbent material such as sand or sawdust.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Specific Gravity	1.22g/ml
Viscosity	6,000 - 12,000 cP
Appearance	Pale yellow liquid



Product Details:

Colour:	Pale Yellow	Pale Yellow
Code:	BDPG05	BDPG10
Size:	5L	10L
Barcode:	5060021368638	5060021368621



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V5 25/03/21
Supersedes: V4 06/02/14