



Never compromise on quality!



# RAPTILE TAPE

## Emergency Repair Tape

### Description

**RAPTILE TAPE is a self-fusing silicone repair product with infinite uses. Resists fuels, oil, acids, solvents, salt water, road salt and UV rays.**

For repairing leaks on plumbing and hoses in a flash. It can be used to insulate electrical wiring and it can withstand a constant working temperature of 200°C.

### Properties:

**Pressure resistant up to 8 Bar.**

**Insulates 8,000 volts.**

**Permanent seal.**

**Waterproof - airtight.**

**Can be applied under water.**

**Never gets gummy or sticky.**

### Uses

Suitable for emergency hose repair, pipe and plumbing repair, electrical insulation, wiring harnesses, corrosion protection, sealing connections & fittings, waterproofing, rigging applications, whipping rope ends, marking lines and chain, emergency O-rings and seals, tool handles and grips and much more!

### Application

1) Wrap **RAPTILE TAPE** around project by stretching and overlapping onto itself. Stretch to at least double its original length to ensure a good bond. For high pressure leaks, stretch to the maximum. The tighter **RAPTILE TAPE** is wrapped, the quicker and stronger the bond.

2) Continue wrapping **RAPTILE TAPE** around project by overlapping so that half the width is covered with the next wrap. The first and last wrap should completely overlap onto the previous wrap for a complete bond. Additional layers may be necessary, and the same process should be used over the previous layers. **RAPTILE TAPE** works on either side.

3) Most hose repairs can be repaired with 3-5 layers in thickness, and wrapping 3 to 5 inches in each direction away from the leak.

4) Repositioning **RAPTILE TAPE** can only be done in

the first few seconds after wrapping. Attempting to reposition **RAPTILE TAPE** after 1 minute or longer is not recommended. **RAPTILE TAPE** is not reusable.

5) Additional **RAPTILE TAPE** can be applied over project at any time in the future.

6) **RAPTILE TAPE** does not stick to the surface of a project, and therefore it does not matter whether the surface is clean or dirty. As long as you can overlap **RAPTILE TAPE** onto itself, it will work, even if the surface is wet, dirty, or oily. You should avoid getting dirt or oil between the layers, however, as this will interfere with the bonding surface. **RAPTILE TAPE** can be cut with a utility knife or scissors, and will never leave any sticky residue behind like traditional adhesive tapes because there's no adhesive!

### Limitations

**RAPTILE TAPE** is not designed to be a permanent repair and there are no guarantees as to how long the repair will last.

### Roll Size

Approx. 2.5cm wide x 3m x 0.5mm roll length.

### Colours

**RAPTILE TAPE** is available in black, red, white, clear and yellow.

### Storage Conditions

For the longest shelf life, it should be kept at room temperature and away from direct light or heat. However, these factors only slightly alter the shelf life. Even when stored improperly, **RAPTILE TAPE** should last for many years. Our customers have reported that our self-fusing silicone kept for decades will still work extremely well!

## Specification Summary

Property	Test Method	Mil Spec Min Performance	Test Results*
Operating temperature range		-65° C to 260° C	-65° C to 260° C
Continuous temperature range		-60° C to 200° C	-60° C to 200° C
Cold Brittle Point		-65° C	-65° C
Hardness Shore A	ASTM D2148	50	50
Tensile Strength, Min.	ASTM D119	700 PSI	950 PSI, +/- 25 PSI
Elongation, Min.	ASTM D119	300%	800%, +/- 50%
Tear Strength, Min.	ASTM D624, Die B	85 ppi	85 ppi
Bond Strength, Min.	MIL-I-46852	2 lbs	12 lbs
Cold Brittle Point, Max.	ASTM D746	-65° C	-65° C
Water Absorbtion, Max.	MIL-I-46852	3% By Weight	3% By Weight
Dielectric Strength, Min.	MIL-I-46852	400 v/mil (8,000 Volts/20mil)	400 v/mil (8,000 Volts/20mil)

\*2009 Imanna Laboratory, Rockledge, Florida

### Container Sizes:

<b>Colour:</b>	Black	Clear	Red	White
<b>Code:</b>	BDRAPBL	BDRAPCL	BDRAPR	BDRAPWH
<b>Barcode:</b>	5060021372581	5060021372574	5060021372598	5060021372567
<b>Size:</b>	2.5cm wide x 3m roll length x 0.5mm thick			

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose..*



Certificate Number: 6152  
ISO 9001  
ISO 14001



**BOND IT**  
Unit G16 River Bank Way, Lowfields Business Park,  
Elland, West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V1 12/7/18  
Supercedes