



Never compromise on quality!



RENDER MESH

Glass fibre woven mesh for reinforcing render and plaster

Description

An alkali resistant glass fibre woven mesh, ideal for the reinforcement of render or basecoat plaster. An ideal anti-crack reinforcement for rendering systems. It is also widely used on external wall insulation systems, roof tiles and carpets.

Offering incredible strength when embedded into wet base coat renders and is light, economical, tear resistant and easy to use. Stabilises surfaces and prevents cracking.

Can also be used:

- as a reinforcement of waterproof membranes, felts and similar roofing materials.
- in conjunction with tile adhesives to distribute stress with ceramic, marble and stone tiles.
- With floor coverings to maintain stability and durability.

Application

Apply an even background coat of render to the required thickness. Place the mesh into the wet render and lightly press in with a trowel to completely cover the mesh. Overlap joints in the mesh by a minimum of 5cm. Trowel over to give the required finish effect. Re-inforcement for waterproof membranes, felts and similar roofing materials. Distributes stress evenly when used with marble, stone and ceramic tiles. Maintains stability and durability when used with floorcoverings.

Coverage

1 roll will cover 50m of substrate at a 1m width.

Storage Conditions

Store in dry conditions

Disposal of Containers

Do not leave empty bags or packaging where they could be harmful to children, animals or the environment. Remove any bags or material to a central disposal point in accordance with local regulations.

Health & Safety

Low hazardous product. Keep out of reach of children. Safety data sheet available for professional user on request, or can be downloaded from www.bond-it.co.uk.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Colour	Pink
Composition	Glass fibre strands
Weight	160gsm
Size	50m length x 1m width
Construction	4x4mm mesh

Container Sizes

Code:	BDRENM
Size:	50M x 1M
Barcode:	5060021371386



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V1 14/07/15