Published: October 2019
Version 1

bond it

Never compromise on quality!

MONSTER TAPE

High Strength Water Resistant Tape

Description

A high strength, water resistant, easy tear all purpose, heavy duty tape with high tack for binding, fixing, sealing, repairing, joining, protecting, marking and much more.

Uses

Rubber based adhesive provides long lasting adhesion on most substrates, and will adhere to rough surfaces.

Can be applied to wet and damp surfaces. Temporary (max. 5 hours) leak repair and water immersion. Will withstand short term water exposure e.g. rain showers.

Do not use on dusty or oily surfaces. It is the users responsibility to determine suitability of use.

Application

1. Ensure surfaces are clean, free from dust and dry.
2. Remove outer packaging from roll of tape.
3. Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
4. Cut with a knife or tear when finished.

Safe Handling Precautions

Flammability: **Non-Flammable**

This product will cause no major hazard or problem to the users health.

Storage

Store in a cool dry place. Protect from sunlight and extremes of temperature. Shelf life: 12 months.

Size

48mm x 11M.

Order Information:

Code:	BDWPT48
Size:	48mm x 11M
Barcode:	5060021372505
Colour:	Black

Specification Summary

Backing	PE laminated synthetic cloth
Adhesive	Natural Rubber
Density	ca. 454g/m²
Thickness	420 microns +/- 10%
Tensile Strength	>180 N
Adhesion to Steel Plate	>5.5N/cm
Temperature Resistance	ca. 2 hours @ 80°C

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.

ISOQAR REGISTERED
UKAS PRODUCT CERTIFICATION 0026
Certificate Number: 6152
ISO 9001
ISO 14001

BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk

bond it