

# DECLARATION OF PERFORMANCE



	Air entraining plasticiser for Masonry Mortar EN934-3 T2					Set accelerating admixture for concrete EN934-3 T6		
	Liquid Mortar Plasticiser (Pink)	Liquid Mortar Plasticiser (Brown)	Power Mix	Integral Water Resistant Plasticiser	Power proof	Powder Mortar Plasticiser	Frostproofer and Rapid Hardener	Power Frost
Dosage per 25kg cement	150ml	125ml	3.9ml	500ml	50ml	7.5g	3.75l	500ml
Maximum Chloride ion content by mass	<0.1%	<0.1%	<0.1%	<0.1%	<0.1%	<0.1%	<0.1%	<0.1%
Maximum Alkali Content by mass	<0.2%	<0.2%	<3.0%	<1.5%	<1.0%	<3.0%	<0.1%	<2%
Corrosion Behaviour-contains only components from EN934-1:2008	Annex A.1	Annex A.1	Annex A.1	Annex A.1	Annex A.1	Annex A.1	Annex A.2 - nitrates	Annex A.2 - nitrates

<b>Audited by</b>	<b>SGS UK Ltd</b>
<b>Auditor ID number</b>	<b>0120</b>
<b>Conformity Level</b>	<b>2+</b>

Phil Radford  
 Technical Manager  
 Seal It Services Ltd T/A Bond It  
 Unit G16 River Bank Way, Lowfields Business Park  
 Elland, West Yorkshire. HX5 9DN. United Kingdom