

DECLARATION OF PERFORMANCE

DOP - BDLEAD

- 1 Identification Code: Bond It FLASH-MATE LEAD SEALANT
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior Use
G Glazing sealant
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 0757
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651-1:2012
Resistance to Flow	≤3mm	Conditioning method B
Loss of Volume	≤30%	Tested on Mortar M1 with primer
Tensile properties after water immersion at 23°C	≥25%	EN15651-2:2012
Tensile properties at maintained extension	Pass	Conditioning method B
Adhesion/cohesion at variable temperatures	Pass	Glass without primer
Adhesion/cohesion at maintained extension after water immersion	Pass	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland
29 Jan 2016

