


**DECLARATION OF PERFORMANCE****DOP - BDPU18**

- 1 Identification Code: Bond It PU18 Polyurethane Adhesive and Sealant  
2. Batch Identification: By batch number – see print on packaging  
3. Intended uses: **F EXT-INT** Façade sealant for External & Internal use. **PW-INT** Sealant for walkways for Internal use.  
4. Manufacturer: Seal It Services t/a Bond It  
Unit G16 River Bank Way  
Lowfields Business Park  
Elland  
West Yorkshire  
HX5 9DN  
5. Authorised Representative: Not applicable  
6. System of assessment and Verification of constancy: System 3  
7. Notified Body: 0074  
8. European Technical Assessment: Not Applicable  
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,4:2012 Conditioning method A Tested on aluminium without primer and Mortar without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤15%	
Tensile properties after water immersion	Pass	
Tensile properties at maintained extension	Pass	
Tear Resistance	Pass	
Elongation at break	≥25%	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford  
Technical Manager  
Elland  
26 June 2014

