

DECLARATION OF PERFORMANCE

Bond It Ceramic Tile Adhesives

EN12004:2007 +A1:2012 Attestation Level 3a and 3

Improved Dispersion Based Tile Adhesives for Internal Tiling

	Aqua-Tile BDTA01, 02, 03	Fix'n'Grout BDTA10,11
	D2	D2
Bond Strength		
Initial Shear Adhesion Strength	≥1N/mm²	≥1N/mm²
Durability		
Shear Adhesion Strength after	≥1N/mm²	≥1N/mm²
Heat Ageing		
Shear Adhesion Strength at	≥1N/mm²	≥1N/mm²
Elevated Temperatures		
Shear Adhesion Strength after	≥0.5N/mm ²	≥0.5N/mm ²
Water Immersion		
Reaction To Fire	Class E	Class E
Release of Dangerous	See MSDS	See MSDS
Substances		

Dispersion Based Tiles Adhesives with reduced slip for Internal Tiling

	Premium	
	CTA	SuperGrip
	BDTA17,18	BDTA07,08,06
	D1T	D1T
Bond Strength		
Initial Shear Adhesion Strength	≥1N/mm²	≥1N/mm²
Durability		
Shear Adhesion Strength after	≥1N/mm²	≥1N/mm²
Heat Ageing		
Reaction To Fire	Class E	Class E
Release of Dangerous	See MSDS	See MSDS
Substances		

Improved Fast Setting Cementitious Tile Adhesive for Internal Tiling

	Rapid-Flex BDTRF/	
	BDTRFWH	
	C2F	
Bond Strength		
Early Tensile Adhesion Strength	≥0.5N/mm ²	
Initial Tensile Adhesion Strength	≥1N/mm²	
Durability		
Tensile Adhesion Strength after	≥1N/mm²	
Water Immersion		
Reaction To Fire	Class E	
Release of Dangerous Substances	See MSDS	

Fast Setting Cementitious Tile Adhesive for Internal Tiling

	Rapid-Set BDTRS
	C1F
Bond Strength	
Early Tensile Adhesion Strength	≥0.5N/mm ²
Initial Tensile Adhesion Strength	≥0.5N/mm ²
Durability	
Tensile Adhesion Strength after Water Immersion	≥0.5N/mm²
Reaction To Fire	Class E
Release of Dangerous Substances	See MSDS

Phil Radford
Technical Manager
Seal It Services
Trading as Bond It
Unit G16 River Bank Way,
Lowfields Business Park
Elland, West Yorkshire
HX5 9DN
United Kingdom