

## **DECLARATION OF PERFORMANCE**


### **DOP – BDGIST WH/T**

- |   |  |
|---|--|
| 1. Identification Code:                                   | Bond It “The One” Silicone   |
| 2. Batch Identification:                                  | By batch number – see print on packaging   |
| 3. Intended uses:   | <b>F EXT-INT</b> Façade Sealant for Exterior and Interior Use<br>25LM. <b>G 25LM</b> Glazing Sealant 25LM. <b>XS1</b> Sanitary<br>Sealant. <b>PW EXT_INT</b> Sealant for exterior and interior<br>Pedestrian Walkways <b>CC</b> suitable for cold climates |
| 4. Manufacturer:  | Seal It Services t/a Bond It<br>Unit G16 River Bank Way<br>Lowfields Business Park<br>Elland<br>West Yorkshire, HX5 9DN  |
| 5. Authorised Representative:                             | Not applicable   |
| 6. System of assessment and Verification of<br>constancy: | System 3   |
| 7. Notified Body:   | 0757   |
| 8. European Technical Assessment:                         | Not Applicable   |
| 9. Declared performance:                                  |  |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2,3,4:2012 Conditioning method A Tested on Mortar M1 without primer, Glass without primer, Aluminium without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties at maintained extension	Pass	
Tensile Properties – secant modulus	<0.9MPa	
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Adhesion/cohesion after exposure to heat, water and artificial light	Pass	
Microbiological Growth	XS1	
Elastic Recovery	>70%	
Tear Resistance	Pass	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford  
Technical Manager  
Elland  
26 June 2014

