

DECLARATION OF PERFORMANCE

DOP - BDLEAD

- | | |
|--|---|
| 1 Identification Code: | Bond It FLASH-MATE LEAD SEALANT |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT Façade Sealant for Exterior and Interior Use G Glazing sealant S1 Sanitary sealant |
| 4. Manufacturer: | Seal It Services t/a Bond It Unit G16 River Bank Way Lowfields Business Park Elland West Yorkshire HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 0757 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

| ESSENTIAL CHARACTERISTIC | DECLARED PERFORMANCE | HARMONISED STANDARD |
|---|----------------------|-----------------------|
| Reaction to Fire | Class E | |
| Release of Chemicals | None | See MSDS |
| Water Tightness and Air Tightness as determined by: | | EN 15651-1:2012 |
| Resistance to Flow | ≤3mm | Conditioning method B |
| Loss of Volume | ≤30% | Mortar M1 with primer |
| Tensile properties at 23°C | ≥25% | EN 15651-2:2012 |
| Tensile properties at maintained extension | NF | Conditioning method B |
| Adhesion/cohesion at variable temperatures | NF | Glass without primer |
| Adhesion/cohesion at maintained extension after water immersion | NF | EN 15651-3:2012 |
| Durability | NF | Conditioning method B |
| Microbiological growth | 1 | Aluminium with primer |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Kayleigh Cox-Nowak
Technical Manager
Elland
25/06/2018

