

Construction Products Regulations (EU) 305 2011

## DECLARATION OF PERFORMANCE DOP - BDSANX

2. Batch Identification: By batch number – see print on packaging

3. Intended uses: FINT Façade Sealant for Interior Use. XS1 Sanitary

Sealant.

4. Manufacturer: Seal It Services t/a Bond It

Unit G16 River Bank Way Lowfields Business Park

Elland

West Yorkshire, HX5 9DN

5. Authorised Representative: Not applicable

6. System of assessment and Verification of

System 3

constancy:

7. Notified Body: 0757

8. European Technical Assessment: Not Applicable

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,3:2012
Resistance to Flow	≤3mm	Conditioning method B
Loss of Volume	≤10%	Tested on Mortar M1 without
Tensile properties – Secant modulus	< 0.4 MPa	primer, Aluminium without
Tensile properties at maintained	Pass	primer
extension		
Adhesion/cohesion at variable	Pass	
temperature		
Adhesion/cohesion after water	Pass	
immersion.		
Microbiological Growth	XS1	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

PROJENS

Phil Radford Technical Manager Elland Issue 2 10 Jan 2017