

DECLARATION OF PERFORMANCE

DOP - WP70

- | | |
|--|---|
| 1. Identification Code: | Bond It WP70 Oxime Silicone |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT Façade Sealant for Interior Use
G Glazing sealant |
| 4. Manufacturer: | Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 0757 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651-1:2012
Resistance to Flow	≤3mm	Conditioning method B
Tensile properties after water immersion at 23°C	≥25%	Tested on Mortar M1 with primer
Tensile properties at maintained extension	Pass	EN15651-2:2012
Adhesion/cohesion at variable temperatures	Pass	Conditioning method B
Adhesion/cohesion at maintained extension after water immersion	Pass	Glass without primer
Durability	Pass	EN15651-2:2012
		Conditioning method B
		Aluminium without primer

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland
21 Aug 2017