


DECLARATION OF PERFORMANCE
ZM10 Silicone

- 1 Identification Code: AS10
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT 25LM.** Façade Sealant for Exterior & Interior Use
G 25LM Glazing Sealant
XS1 Sanitary
PW EXT-INT 25LM Walkway sealant for Exterior & Interior use
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 0757
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
<i>Reaction to Fire</i>	<i>Class E</i>	
<i>Release of Chemicals</i>	<i>None</i>	<i>See MSDS</i>
Water Tightness and Air Tightness as determined by:		<i>BS EN 15651-1:2012 Conditioning method B Tested on Mortar M1 without primer. EN 15651-2:2012 Conditioning method B Glass without primer. EN15651-3:2012 Conditioning method B Aluminium without primer. EN15651-4:2012 Conditioning method B Aluminium without primer</i>
<i>Resistance to Flow</i>	<i>≤3mm</i>	
<i>Elastic Recovery</i>	<i>>70%</i>	
<i>Loss of Volume</i>	<i>≤10%</i>	
<i>Tensile Properties Secant Modulus</i>	<i><0.4 MPa</i>	
<i>Tensile properties at maintained extension</i>	<i>NF</i>	
<i>Adhesion/cohesion at variable temperatures</i>	<i>NF</i>	
<i>Adhesion/cohesion at maintained extension after water immersion</i>	<i>NF</i>	
<i>Adhesion/cohesion after exposure to heat, water and artificial light</i>	<i>NF</i>	
<i>Tear Resistance</i>	<i>NF</i>	
<i>Microbiological Growth</i>	<i>1</i>	
<i>Durability</i>	<i>NF</i>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland
13 Sept 2017