



Never compromise on quality!



# PC100 INHIBITOR

## Liquid

### Description

*A high performance inhibitor against formation of scale, rust corrosion, hydrogen gassing, microbiological growth and boiler noise.*

### Uses

**PC100 INHIBITOR** is suitable for all metals including aluminium. Once added PC100 does not need to be replaced unless the system is drained down.

### Application

Filling the system: Open systems should be dosed via the filling and expansion tank. If system is full, draining at a low point should be carried out to ensure product enters the circulatory system. Sealed systems should be filled via filling loop or a drained radiator.

Dosage: PC100 for optimum efficiency should be dosed @1% of system volume i.e. 1L per 100L of system water. Generally 1 bottle contains enough chemical for a typical system with a 14.5Kw Boiler (50,000 Btu/hr) domestic hot water cylinder and up to 10 radiators. For larger systems an extra bottle will be required - overdosing will not cause any problems or detrimental affects to the system.

Please note: where a thermal storage appliance is fitted allowance must be made for the extra volume of primary water. The concentration can be checked with a conductivity meter.

### LIMITATIONS

**DO NOT ADD TO PRIMATIC SYSTEM.**

### Storage Conditions

Store in cool, dry conditions in tightly sealed container. Store above +5°C and below +30°C. Do not allow to freeze.

### Shelf Life

12 months in original, unopened containers.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

### Safe Handling Precautions

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

*Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.*

## Specification Summary

Flashpoint	None
Appearance	Light coloured
Odour	Faint
Specific Gravity	1.05
pH	7.3

## Container Sizes

<b>Code:</b>	BDPC100
<b>Size:</b>	1L
<b>Barcode:</b>	5060021367495

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number: 6152  
ISO 9001  
ISO 14001



**BOND IT**  
Unit G16 River Bank Way, Lowfields Business Park, Elland,  
West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: [sales@bond-it.co.uk](mailto:sales@bond-it.co.uk) Website: [www.bond-it.co.uk](http://www.bond-it.co.uk)



V1 30/7/2009  
Supersedes V